

Appl. No. 09/369,790
Reply to Examiner's Action dated 03/23/2006

IN THE CLAIMS:

1. (Currently Amended) A computer-based system for validating an interface of a dynamically linkable component, comprising:

a check code generator that employs filtering directives to include or exclude textual interface information to transform ~~transforms~~ said interface of said dynamically linkable component into an interface identifier representing said interface and couples said interface identifier to said dynamically linkable component; and

an interface verifier that employs said interface identifier to determine a compatibility of said interface of said dynamically linkable component by comparing said interface identifier with an interface identifier history list representing a history of modifications to said interface, said history list containing at least one member.

2. (Original) The system as recited in Claim 1 wherein said check code generator transforms said interface of said dynamically linkable component into said interface identifier by transforming a textual representation of at least a portion of said interface.

3. (Original) The system as recited in Claim 1 wherein said check code generator couples said interface identifier to said dynamically linkable component by placing said interface identifier in a types declaration file.

4. (Original) The system as recited in Claim 1 wherein said interface identifier varies as a function of a version of said dynamically linkable component.

Appl. No. 09/369,790
Reply to Examiner's Action dated 03/23/2006

5. (Original) The system as recited in Claim 1 wherein said interface verifier employs said interface identifier to determine a compatibility of said dynamically linkable component with a second dynamically linkable component.

6. (Original) The system as recited in Claim 1 wherein said interface verifier is a part of a second dynamically linkable component.

7. (Previously Presented) The system as recited in Claim 1 wherein said history list contains at least two members.

8. (Original) The system as recited in Claim 1 wherein said interface identifier is a type selected from the group consisting of:

- a check sum, and
- a cyclic redundancy check.

9. (Cancelled)

10. (Currently Amended) A computer-implemented method of validating an interface of a dynamically linkable component, comprising:

employing filtering directives to include or exclude textual interface information to transform
transforming said interface of said dynamically linkable component into an interface identifier representing said interface;

- coupling said interface identifier to said dynamically linkable component; and
- employing said interface identifier to determine a compatibility of said interface of said

Appl. No. 09/369,790
Reply to Examiner's Action dated 03/23/2006

dynamically linkable component by comparing said interface identifier with an interface identifier history list representing a history of modifications to said interface, said history list containing at least one member.

11. (Original) The method as recited in Claim 10 wherein said transforming comprises transforming a textual representation of at least a portion of said interface.

12. (Original) The method as recited in Claim 10 wherein said coupling comprises placing said interface identifier in a types declaration file.

13. (Original) The method as recited in Claim 10 wherein said interface identifier varies as a function of a version of said dynamically linkable component.

14. (Original) The method as recited in Claim 10 wherein said employing comprises employing said interface identifier to determine a compatibility of said dynamically linkable component with a second dynamically linkable component.

15. (Original) The method as recited in Claim 10 wherein said interface verifier is a part of a second dynamically linkable component.

16. (Previously Presented) The method as recited in Claim 10 wherein said history list contains at least two members.

Appl. No. 09/369,790
Reply to Examiner's Action dated 03/23/2006

17. (Original) The method as recited in Claim 10 wherein said interface identifier is a type selected from the group consisting of:

- a check sum, and
- a cyclic redundancy check.

18. (Cancelled)

19. (Currently Amended) A computer-based system for validating an interface of a dynamically linkable component, comprising:

an interface identifier, generated by filtering textual information present in said interface and coupled to said dynamically linkable component, that represents said interface of said dynamically linkable component; and

an interface verifier that employs said interface identifier to determine a compatibility of said interface of said dynamically linkable component by comparing said interface identifier with an interface identifier history list representing a history of modifications to said interface, said history list containing at least one member.

20. (Original) The system as recited in Claim 19 wherein said interface identifier is contained within a types declaration file.

21. (Original) The system as recited in Claim 19 wherein said interface identifier varies as a function of a version of said dynamically linkable component.

Appl. No. 09/369,790
Reply to Examiner's Action dated 03/23/2006

22. (Original) The system as recited in Claim 19 wherein said interface verifier employs said interface identifier to determine a compatibility of said dynamically linkable component with a second dynamically linkable component.

23. (Original) The system as recited in Claim 19 wherein said interface verifier is a part of a second dynamically linkable component.

24. (Previously Presented) The system as recited in Claim 19 wherein said history list contains at least two members.

25. (Currently Amended) A computer-implemented method of validating an interface of a dynamically linkable component, comprising:

generating an interface identifier by employing filtering directives to include or exclude textual information present in said interface;

coupling ~~an~~ said interface identifier to said dynamically linkable component; and

employing said interface identifier to determine a compatibility of said interface of said dynamically linkable component by comparing said interface identifier with an interface identifier history list representing a history of modifications to said interface, said history list containing at least one member.

26. (Original) The method as recited in Claim 25 wherein said coupling comprises placing said interface identifier in a types declaration file.

Appl. No. 09/369,790
Reply to Examiner's Action dated 03/23/2006

27. (Original) The method as recited in Claim 25 wherein said interface identifier varies as a function of a version of said dynamically linkable component.

28. (Original) The method as recited in Claim 25 wherein said employing comprises employing said interface identifier to determine a compatibility of said dynamically linkable component with a second dynamically linkable component.

29. (Original) The method as recited in Claim 25 wherein said interface verifier is a part of a second dynamically linkable component.

30. (Previously Presented) The method as recited in Claim 25 wherein said history list contains at least two members.

31. (Currently Amended) A real-time process control system, comprising:

a plurality of sensors and controllable devices;

a controller, coupled to said plurality of sensors and controllable devices, that executes software having at least first and second dynamically linkable components to coordinate an operation of said plurality of sensors and controllable devices;

an interface identifier, generated by filtering textual information present in said interface and coupled to said first dynamically linkable component, that represents an interface of said first dynamically linkable component; and

an interface verifier that employs said interface identifier to determine a compatibility of said interface of said first and second dynamically linkable components by comparing said interface identifier with a history list representing a history of modifications to said interface,

Appl. No. 09/369,790
Reply to Examiner's Action dated 03/23/2006

said history list associated with said second dynamically linkable component and containing at least one member.

32. (Original) The real-time process control system as recited in Claim 31 wherein said interface identifier is a transformation of a textual representation of at least a portion of said interface.

33. (Original) The real-time process control system as recited in Claim 31 wherein said interface identifier is contained within in a types declaration file.

34. (Original) The real-time process control system as recited in Claim 31 wherein said interface identifier varies as a function of a version of said first dynamically linkable component.

35. (Original) The real-time process control system as recited in Claim 31 wherein said interface verifier is a part of said second dynamically linkable component.

36. (Previously Presented) The real-time process control system as recited in Claim 31 wherein said history list is associated with said second dynamically linkable component and contains at least two members.

37. (Original) The real-time process control system as recited in Claim 31 wherein said interface identifier is a type selected from the group consisting of:

a check sum, and

a cyclic redundancy check.

Appl. No. 09/369,790

Reply to Examiner's Action dated 03/23/2006

38. (New) The system as recited in Claim 1 wherein said filtering directives are configured to substantially avoid alpha and beta errors.

39. (New) The method as recited in Claim 10 wherein said employing filtering directives substantially avoids alpha errors.